

**CLAIMS**

1. A container, comprising:
  - a body including
    - a first end, the first end being closed,
    - a second end including an opening configured to allow objects to be
  - placed inside the container,
  - an inner surface, and
  - an outer surface; and
  - a loop attached to the body at at least two separate points, the loop configured to form a first handle for the container, the handle having a first size, the loop further configured to allow the loop to form a pair of second handles for the container, the pair of second handles having a second size.
2. The container of claim 1,
  - wherein the first size is substantially greater than the second size.
3. The container of claim 1,
  - wherein the loop comprises a cord with a first cord end and a second cord end, the first cord end joined to the second cord end.
4. The container of claim 1,
  - wherein the loop comprises a cord with a first cord end and a second cord end, the first cord end attached to the inner surface of the body at a first one of the least two separate points and the second cord end attached to the inner surface of the body at a second one of the least two separate points.
5. The container of claim 1, wherein
  - the loop is further configured to allow the loop to form a decoration wrapped around the outer surface of the body.
6. The container of claim 1, wherein
  - the at least two separate points are located on the inner surface of the body.

7. The container of claim 1, further comprising,  
an attachment joined to the inner surface of the body, the attachment  
configured to attach the loop to the inner surface of the body at a first one of the least  
5 two separate points.
8. The container of claim 7, further comprising  
a second attachment joined to the inner surface of the body, the second  
attachment configured to attach the loop to the inner surface of the body at a second  
10 one of the least two separate points.
9. The container of claim 1, wherein  
the body further includes two pairs of holes in the inner surface and the loop is  
attached to the body by threading the loop through the two pairs of holes.  
15
10. The container of claim 1, wherein  
the loop is configured to allow the loop to be detached from the body of the  
container.
- 20 11. The container of claim 1, wherein  
the body of the container is constructed from a single sheet of material.
12. The container of claim 1, wherein  
the first end is welded closed.  
25
13. The container of claim 1, wherein  
the body further includes a closable top, the closable top configured to allow  
the opening in the second end of the body to be closed.
- 30 14. The container of claim 1, wherein  
the body comprises a sheet of laminate including a layer of metal.

15. A container, comprising:

a body including

a closed first end,

a second end including an opening configured to allow objects

5 to be placed inside the container,

an inner surface,

an outer surface, and

a closable top configured to allow the opening in the second

end of the body to be closed;

10 a loop attached to the body at at least two separate points on the inner surface of the body, the loop configured to form a first handle for the container, the first handle having a first size, the loop further configured to allow the loop to form a pair of second handles for the container, the pair of second handles each having a second size, the first size more than twice the second size, the loop further configured  
15 to allow the loop to form a decoration wrapped around the outer surface of the body; and

an attachment joined to the inner surface of the body, the attachment configured to attach the loop to the inner surface of the body.